

HIKVISION

لیست قیمت رسمی نیمه اردیبهشت ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

1

2

3

4

5

6

Click for More information

DS-2CE16D0T-ITPF(2.8mm)

DS-2CE16D0T-ITPFS

DS-2CE16D0T-ITFS

DS-2CE16D0T-EXIF

DS-2CE16D0T-EXIPF

DS-2CE16D3T-ITF



Price (Rials)

1٠,٧٣٥,٠٠٠

1٤,٣٩٠,٠٠٠

1٧,٤٢٠,٠٠٠

1٢,٩٨٠,٠٠٠

1٢,٤٠٠,٠٠٠

٢1,٤٤٠,٠٠٠

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.02Lux/F1.2

0.02Lux/F1.2

0.02Lux/F1.2

Lens

2.8mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6mm Fixed

2.8/3.6mm Fixed

2.8/3.6mm Fixed

Viewing Angle

106.4°

106.4°/79.6° /51.9°

106.4°/79.6° /51.9°

102°/81°

96.5°/76.9°

106°/82°

IR Range

Up to 25m

Up to 25m (Exir)

Up to 30m (Exir)

Up to 20m

Up to 20m (Exir)

Up to 30m (Exir)

Body Type

Plastic

Plastic

Metal

Metal

Plastic

Metal

IP Standard

IP67

IP67

IP67

IP66

IP66

IP67

OSD Menu

No

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

Yes (120db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, HLC, DNR, BLC, 2D DNR, Switchable

Smart IR, Switchable, Built in mic

HLC,2D DNR, BLC, Switchable, Built-in microphone

2D DNR, BLC, Switchable

2D DNR, BLC, AGC, Switchable

3D DNR,HLC, BLC, Switchable

7

8

9

10

11

12

Click for More
information

DS-2CE16D3T-IT3F(2.8mm)

DS-2CE17D0T-IT1F

DS-2CE17D0T-IT3F(2.8mm)

DS-2CE10DF3T-F

DS-2CE10DF3T-FS(2.8mm)

DS-2CE12DF3T-F(3.6mm)



Price (Rials)

١٩,٤٧٠,٠٠٠

١٨,٠٥٠,٠٠٠

٢٣,١٦٠,٠٠٠

٢٣,٧٥٠,٠٠٠

٣٤,٧٠,٠٠٠

٢٩,٤١٠,٠٠٠

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.005Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.0005Lux/F1.0

0.0005Lux/F1.0

0.0005Lux/F1.0

Lens

2.8mm Fixed

2.8/3.6mm Fixed

2.8mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

3.6mm Fixed

Viewing Angle

106°

101°/79.6°

106.4°

98°/77° /51°

98°

77°

IR Range

Up to 50m (Exir)

Up to 30m (Exir)

Up to 40m

Up to 20m (ColorVu)

Up to 20m (ColorVu)

Up to 40m (ColorVu)

Body Type

Metal

Metal & Plastic

Metal & Plastic

Metal

Metal

Metal

IP Standard

IP67

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

No

No

WDR

Yes (120db)

DWDR

DWDR

Yes (130db)

Yes (130db)

Yes (130db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

3D DNR,HLC, BLC,
Switchable3D DNR,HLC, BLC, AGC,
Switchable

HLC, BLC, AGC, Switchable

HLC, BLC, Smart IR,
Switchable, 3D DNRHLC, BLC, Smart IR,
Switchable, 3D DNR, Built
in micHLC, BLC, Smart IR,
Switchable, 3D DNR

13

14

15

16

17

18

Click for More
information

DS-2CE12DF3T-FS(2.8mm)


DS-2CE76D0T-ITPF(C)

DS-2CE76D0T-EXIPF(2.8mm)

DS-2CE76D0T-ITPFS

DS-2CE76D0T-ITMF

DS-2CE76D0T-ITMFS



Price (Rials)	٣٨,٣٣٠,٠٠٠	١١,٢٥٠,٠٠٠	١٣,٣٩٠,٠٠٠	١٢,٨٤٠,٠٠٠	١٦,٢٢٠,٠٠٠	١٨,٨١٠,٠٠٠
Camera Type	Bullet	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.0005Lux/F1.0	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2
Lens	2.8mm Fixed	2.8/3.6/6mm Fixed	2.8mm Fixed	2.8/3.6/6mm Fixed	2.8mm Fixed	2.8/3.6/6mm Fixed
Viewing Angle	98°	103°/82.2° /54°	96.5°	106°/79.6°/51°	101°	106.4°/79.6°/51.9°
IR Range	Up to 40m (ColorVu)	Up to 20m (Exir)	Up to 20m (Exir)	Up to 20m (Exir)	Up to 30m	Up to 30m (Exir)
Body Type	Metal	Plastic	Plastic	Plastic	Metal	Metal
IP Standard	IP67	IP66	IP66	IP66	IP67	IP67
OSD Menu	No	No	No	No	No	No
WDR	Yes (130db)	DWDR	DWDR	DWDR	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	HLC, BLC, Smart IR, Switchable, 3D DNR, Built in mic	Smart IR, HLC,BLC, Switchable	Smart IR, HLC,BLC, Switchable	Smart IR, HLC,BLC, Switchable	Smart IR, ICR, HLC,BLC, 2D DNR, Switchable	ICR,AGC, Switchable, Built in mic

19

20

21

22

23

24

Click for More
information

DS-2CE76D3T-ITPF

DS-2CE78D0T-IT3FS

DS-2CE76D3T-ITMF(2.8mm)

DS-2CE56D0T-VFIR3F

DS-2CE72DFT-FC

DS-2CE70DF0T-PF



Price (Rials)

1٧,٢٢٠,٠٠٠

٢٣,٨٢٠,٠٠٠

٢٣,٨٢٠,٠٠٠

٣٢,٢٢٠,٠٠٠

1٩,٧٠٠,٠٠٠

٢٢,٧٢٠,٠٠٠

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.005Lux/F1.2

0.01Lux/F1.2

0.005Lux/F1.2

0.01Lux/F1.2

0.0008Lux/F1.0

0.001Lux/F1.0

Lens

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

2.8 - 12mm VariFocal

3.6/6mm Fixed

2.8/3.6/6mm Fixed

Viewing Angle

106°/82° /51°

106.4°/79.6° /51.9°

106°

105°/ 32°

83°/51°

98°/76°/50°

IR Range

Up to 30m(Exir)

Up to 40m(Exir)

Up to 30m(Exir)

Up to 40m

Up to 20m (ColorVu)

Up to 20m (ColorVu)

Body Type

Plastic

Metal & Plastic

Metal

Metal & Plastic

Metal & Plastic

Plastic

IP Standard

IP66

IP67

IP67

IP66

IP67

IP66

OSD Menu

Yes

No

No

No

No

No

WDR

Yes (120db)

DWDR

Yes (120db)

DWDR

Yes (120db)

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, HLC,BLC,
SwitchableSmart IR, AGC, Switchable,
ICR, Built in micSmart IR, HLC,BLC,
Switchable, 3D DNRSmart IR, ICR, AGC,
Switchable3D DNR, HLC,BLC,
Switchable

AGC, Switchable

25

26

27

28

29

30

Click for More
information

DS-2CE70DF3T-PF(3.6mm)


DS-2CE72DF3T-F

DS-2CE16H0T-ITPF

DS-2CE16H0T-ITPFS

DS-2CE16H0T-ITF

DS-2CE16H0T-ITFS



Price (Rials)

٢٩,٩٨٠,٠٠٠

٢٥,٤١٠,٠٠٠

١٧,٧٣٠,٠٠٠

٢٠,٧٧٠,٠٠٠

١٩,٢٧٠,٠٠٠

٢٣,٠٥٠,٠٠٠

Camera Type

Dome

Dome

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

2 Megapixel

2 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

Resolution

HD1080P

HD1080P

5MP (2560*1944)

5MP (2592*1944)

5MP (2592*1944)

5MP (2560*1944)

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.0005Lux/F1.0

0.0005Lux/F1.0

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1

0.01Lux/F1

Lens

3.6mm Fixed

2.8/3.6mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

Viewing Angle

77°

98°/77°

85.5°/80.1°/57.1°

85.5°/80.1°/57.1°

85.5°/80.1°/57.1°

85.5°/80.1°/57.1°

IR Range

Up to 20m (ColorVu)

Up to 40m (ColorVu)

Up to 20m (Exir)

Up to 25m (Exir)

Up to 20m (Exir)

Up to 30m (Exir)

Body Type

Plastic

Metal & Plastic

Plastic

Plastic

Metal

Metal

IP Standard

IP66

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

Yes

No

WDR

Yes (130db)

Yes (130db)

DWDR

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

AGC, Switchable, 3D DNR

AGC, Switchable, 3D DNR

Smart IR, BLC,AGC, DNR,
SwitchableSmart IR, HLC,BLC,AGC, 2D
DNR, Switchable, Built in
Mic2D DNR, DWDR,
Switchable2D DNR, Switchable,
Built in Mic

31

32

33

34

35

36

Click for More
information

DS-2CE17H0T-IT1F


DS-2CE17H0T-IT3F

DS-2CE17H0T-IT3FS(2.8mm)

DS-2CE17H0T-IT5F

DS-2CE56H0T-IT1F

DS-2CE76H0T-ITPF(2.8mm)



Price (Rials)

۲۳,۲۳۰,۰۰۰

۲۳,۳۰۰,۰۰۰

۲۹,۷۹۰,۰۰۰

۲۴,۲۹۵,۰۰۰

۲۰,۹۰۰,۰۰۰

۱۶,۳۰۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Dome

Dome

Imaging Sensor

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

Resolution

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

Lens

2.4/2.8/3.6mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

3.6/6/8mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

Viewing Angle

110°/85°/80°

85°/80°/57°

85°

80°/57°/41°

105°/85°/65°

110°/85°/80°

IR Range

Up to 30m

Up to 40m

Up to 40m

Up to 80m

Up to 20m (Exir)

Up to 20m (Exir)

Body Type

Metal & Plastic

Plastic

IP Standard

IP67

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

Yes

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, 2D DNR,
HLC,BLC, SwitchableSmart IR, ICR, AGC, BLC,
SwitchableSmart IR, ICR, AGC, BLC,
HLC

37

38

39

40

41

42

Click for More
information

DS-2CE76H0T-ITPFS

DS-2CE76H0T-ITMF

DS-2CE76H0T-ITMFS

DS-2CE78H0T-IT1F(2.4mm)

DS-2CE78H0T-IT3F

DS-2CE72HFT-F28(2.8mm)



Price (Rials)

۲۰,۲۸۰,۰۰۰

۲۱,۴۴۰,۰۰۰

۲۴,۲۹۰,۰۰۰

۲۳,۸۶۰,۰۰۰

۲۵,۷۹۰,۰۰۰

۳۸,۳۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

Resolution

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HD-TVI

Min. Illustration

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.0005 Lux/F1.0

Lens

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

2.4 mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

Viewing Angle

85°/80°/57.1°

105°/85°/65°

85°

110°

85°/80°/57°

99.7°

IR Range

Up to 20m (Exir)

Up to 30m (Exir)

Up to 30m

Up to 30m (Exir)

Up to 40m (Exir)

Up to 20m (ColorVu)

Body Type

Plastic

Metal

Metal

Metal & Plastic

Metal & Plastic

Metal & Plastic

IP Standard

IP67

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

Yes (130db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, ICR, AGC, Built in Mic

Smart IR, ICR, AGC, BLC, Switchable

Smart IR, ICR, AGC, BLC, Switchable, Built in mic

Smart IR, ICR, AGC, BLC,HLC, Switchable

Smart IR, ICR, AGC,HLC, BLC, Switchable

Smart IR, 3D DNR

43

44

45

46

47

Click for More
information

DS-2CE72KF0T-FS(2.8mm)

DS-2CE10KF0T-FS(2.8mm)

DS-2CE12KF0T-FS(2.8mm)

DS-2CE78U8T-IT3

DS-2AE4225TI-D



Price (Rials)

۳۷,۴۰۰,۰۰۰

۳۴,۸۱۰,۰۰۰

۴۰,۲۶۰,۰۰۰

۶۳,۸۷۰,۰۰۰

۱۸۰,۵۲۰,۰۰۰

Camera Type

Dome

Bullet

Bullet

Dome

PTZ

Imaging Sensor

3K

3K

3K

8.29 Megapixel

2 Megapixel

Resolution

3K (2960*1665)

3K (2960*1665)

3K (2960*1665)

8MP (3840*2160)

1920 × 1080

Signal System

HD-TVI

HD-TVI

HD-TVI

HD-TVI

HD-TVI

Min. Illustration

0.001 Lux/F1.0

0.001 Lux/F1.0

0.001 Lux/F1.0

0.003 Lux/F1.2

0.005 Lux/F1.6

Lens

2.8mm Fixed

2.8mm Fixed

2.8mm Fixed

2.8/3.6/6mm Fixed

4.8 mm-120mm

Viewing Angle

102°

102°

102°

105°/85°/65°

25x Optical Zoom

IR Range

Up to 40m (ColorVu)

Up to 20m (ColorVu)

Up to 40m (ColorVu)

Up to 60m (Exir)

Up to 100m

Body Type

Metal & Plastic

Metal & Plastic

Metal

Metal & Plastic

Metal

IP Standard

IP67

IP67

IP67

IP67

IP66

OSD Menu

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

Yes (120db)

Yes (120db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, 3D DNR, Built in mic

Smart IR, 2D DNR, Built in mic

Smart IR, 2D DNR, Built in mic

Smart IR, ICR

Smart IR, ICR, Switchable, DarkFighter

48

49

50

51

52

53

Click for More information

IDS-7204HQHI-M1/S

IDS-7208HQHI-M1/S

DS-7216HQHI-K1

DS-7216HQHI-M1/S

IDS-7216HQHI-M2/S

DS-7232HQHI-K2



Price (Rials)

۴۶,۵۲۰,۰۰۰

۷۱,۲۹۰,۰۰۰

۱۲۱,۷۵۷,۵۰۰

۱۰۹,۷۷۰,۰۰۰

۱۵۱,۱۵۰,۰۰۰

۲۶۷,۳۲۰,۰۰۰

DVR Type

4+1 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP8+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP32+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP

Analog Video Input

4 Ch. HDTV/Analog
Up to 4MP8 Ch. HDTV/Analog
Up to 4MP16 Ch. HDTV/Analog
Up to 4MP16 Ch. HDTV/Analog
Up to 4MP16 Ch. HDTV/Analog
Up to 4MP32 Ch. HDTV/Analog
Up to 4MP

IP Video Input

1 Ch. Up to 6MP

2 Ch. Up to 6MP

Audio Input/Output

1Ch. In / 1Ch. Out

Recording

4MP: 15FPS
3MP: 15FPS
1080P: 15FPS4MP: 15FPS
3MP: 15FPS
1080P: 15FPS4MP: 15FPS
3MP: 15FPS
1080P: 15FPS3K: 30FPS
5MP: 20FPS
1080P: 30FPS4MP: 15FPS
3MP: 15FPS
1080P: 15FPS4MP: 15FPS
3MP: 15FPS
1080P: 15FPS

Video Output

1 Port HDMI 1080P
1 Port VGA,
1Ch. CVBS1 Port HDMI 1080P
1 Port VGA,
1Ch. CVBS1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS1 Port HDMI 1080P
1 Port VGA
1Ch. CVBS1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS

SATA Interface

1 HDD up to 10TB

2 HDD up to 10TB

2 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265/H.265+
Compression, ONVIF,
Smart SearchH.265/H.265+
Compression, ONVIF,
Smart SearchH.265/H.265+
Compression, ONVIF,
VCA, Smart SearchH.265/H.265 pro+
Compression, ONVIF,
VCA, Smart SearchH.265/H.265+
Compression, ONVIF,
VCA, Smart SearchH.265 Pro+/H.265
Pro/H.265/ Compression,
VCA

54

55

56

57

58

59

Click for More
information

IDS-7232HQHI-M2/S


DS-7204HUHI-K1

DS-7204HUHI-K1/P

DS-7204HUHI-M1/S

DS-7208HUHI-M1/S

DS-7216HUHI-K2



Price (Rials)

۲۵۰,۰۰۰,۰۰۰

۶۷,۷۲۰,۰۰۰

۶۷,۴۰۰,۰۰۰

۷۴,۷۲۰,۰۰۰

۱۲۰,۶۱۰,۰۰۰

۲۱۸,۷۳۰,۰۰۰

DVR Type

32+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4+4 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP8+4 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+16Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP

Analog Video Input

32 Ch. HDTV/Analog
Up to 4MPSupport
Up to 5MP resolution
recordingSupport
Up to 5MP resolution
recording

IP Video Input

2 Ch. Up to 6MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

4 Ch. Up to 8MP

8 Ch. Up to 8MP

Audio Input/Output

1Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

Recording

4MP: 15FPS
3MP: 15FPS
1080P: 15FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 30FPS
4MP: 30FPS
3mp: 30FPS5MP: 20FPS
4MP: 25FPS
3mp: 18FPS

Video Output

1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS1 Port HDMI : 1080P
1 Port VGA1 Port HDMI : 1080P
1 Port VGA
CVBS: PAL1 Port HDMI : 2K
1 Port VGA
CVBS: PAL1 Port HDMI : 4K
1 Port VGA1 Port HDMI : 4K
1 Port VGA
CVBS: PAL

SATA Interface

2 HDD up to 10TB

1 HDD up to 10TB

2 HDD up to 10TB

Network Interface

1 RJ45 1000M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265/H.265+
Compression, ONVIF,
VCA, Smart SearchH.265/H.265+ COMPR
Alarm In/Out : 4/1
Onvif, VCAH.265/H.265+ COMPR
Alarm In/Out : 4/1
Built-in PoCH.265/H.265+ COMPR
Alarm In/Out : N/AH.265 Pro+/H.265 Pro,
OnvifH.265/H.265+ COMPR
Alarm In/Out : 16/4

Click for More
information

IDS-7216HUHI-M2/S



Price (Rials)	۲۲۴,۰۰۰,۰۰۰
DVR Type	16+8 Ch. quadruple Hybrid HD-TVI / AHD / Analog / IP
Analog Video Input	Support Up to 5MP resolution recording
IP Video Input	8 Ch. Up to 8MP
Audio Input/Output	4Ch. In / 1Ch. Out
Recording	5MP: 20FPS 4MP: 25FPS 3mp: 18FPS
Video Output	1 Port HDMI : 4K 1 Port VGA CVBS: PAL
SATA Interface	2 HDD up to 10TB
Network Interface	1 RJ45 1000M
Chassis	Standalone 1U
Other Features	H.265/H.265+ COMPR Alarm In/Out : N/A

HIKVISION

لیست قیمت رسمی نیمه اردیبهشت ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

1

2

3

4

5

6

Click for More
information

DS-2CD1023G0E-I


DS-2CD1023G0-IUF

DS-2CD1043G0-I

DS-2CD1057G0-L

DS-2CD1123G0E-I

DS-2CD1323G0E-I



Price (Rials)

۲۸,۹۰۰,۰۰۰

۴۰,۷۷۰,۰۰۰

۴۲,۳۱۰,۰۰۰

۵۸,۸۶۰,۰۰۰

۲۹,۹۱۰,۰۰۰

۲۹,۵۹۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Dome

Dome

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

4MP(2560x1440/20fps)

5MP (2560 x 1920/20fps)

2MP(1920x1080/30FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.001Lux @ F1.0

0.01Lux @ F1.2

0.01Lux @ F2.0

Lens

2.8/4 mm Fixed

Viewing Angle

112.1°/90.2°

112.1°/90.2°

98°/78.7°

95°/76°

114.8°/86°

105°/81°

IR Range

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (EXIR)

Body Type & Standard

Plastic / IP67

Metal/Plastic / IP67

Plastic / IP67

Metal / IP67

Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256G)

No

Yes (Up to 256G)

No

No

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

DWDR

DWDR

DWDR

Yes (120db)

DWDR

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+
COMP,PIR3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP,PIR3D DNR, BLC, HLC, ROI, H.265+
COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+
COMP

7

8

9

10

11

12

Click for More information

DS-2CD1353G0-I (2.8mm)


DS-2CD1357G0-L

DS-2CD1143G0-I

DS-2CD1143G0-IUF

DS-2CD1153G0-I

DS-2CD2021G1-I (2.8mm)



Price (Rials)

۵۷,۰۰۰,۰۰۰

۵۸,۷۹۰,۰۰۰

۴۷,۴۶۰,۰۰۰

۵۵,۹۶۰,۰۰۰

۵۴,۵۴۰,۰۰۰

۴۹,۹۸۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Bullet

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

5MP(2560x1920/20FPS)

5MP(2560x1920/20FPS)

4MP(2560x1440/20fps)

4MP(2560x1440/20fps)

5MP(2560x1920/15FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F2.0

0.001Lux @ F1.0

0.028Lux @ F2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.005Lux @ F1.6

Lens

2.8 mm Fixed

2.8/4 mm Fixed

Viewing Angle

98.0°

95°/76°

98°/78.7°

98°/78.7°

98°/75.3°

111.6°/91.5°

IR Range

Up to 30m (EXIR)

Up to 30m (Color Vu)

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (EXIR)

Body Type & Standard

Metal/Plastic / IP67

Metal/Plastic / IP67

Plastic / IP67

Plastic / IP67/ IK10

Plastic / IP67/ IK10

Metal/Plastic / IP67

SD Card Support

No

No

No

Yes (Up to 256 G)

No

Yes (Up to 256 G)

Microphone Support

No

No

No

Yes (Built in MIC)

No

No

WDR

Yes (120db)

Yes (120db)

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, VCA, H.265+ COMP

3D DNR, BLC, ROI, VCA, H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, H.265+ COMP

13

14

15

16

17

18

Click for More information

DS-2CD2H25FWD-IZS


DS-2CD2027G2-L (2.8mm)

DS-2CD2043G2-I (2.8mm)

DS-2CD2043G2-IU(2.8mm)

DS-2CD2047G2-L

DS-2CD2063G2-I



Price (Rials)

۱۳۸,۸۷۰,۰۰۰

۷۱,۰۴۰,۰۰۰

۶۶,۴۶۰,۰۰۰

۷۹,۰۷۰,۰۰۰

۷۷,۷۰۰,۰۰۰

۷۲,۷۷۲,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.4" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/30fps)

4MP(2560x1440/30fps)

4MP(2560x1440/30fps)

6MP(2560x1440/30fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

Lens

2.8-12mm Motorized

2.8 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

105°~35°

107°

103°

103°

112°/95°

105°/78°

IR Range

Up to 30m

Up to 40m (Color Vu)

Up to 40m

Up to 40m

Up to 40m (Color Vu)

Up to 40m

Body Type & Standard

Metal / IP66/IK10

Metal / IP67

SD Card Support

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 512 G)

Microphone Support

Yes (1.ch Audio Input)

No

No

Yes (Built in MIC)

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, ROI, HLC, H.265+ COMP, DarkFighter

3D DNR, BLC, HLC, H.265+ COMP

19

20

21


22

23

24

Click for More information

DS-2CD2087G2-LU (2.8mm) DS-2CD2126G2-ISU(2.8mm) DS-2CD2347G2-L(2.8mm) DS-2CD2347G2-LU(2.8mm) DS-2CD2143G2-IU DS-2CD2163G2-IU



Price (Rials)

۱۵۶,۵۵۰,۰۰۰

۸۱,۵۴۰,۰۰۰

۷۸,۹۱۰,۰۰۰

۸۹,۷۶۰,۰۰۰

۶۱,۵۰۰,۰۰۰

۶۹,۰۰۰,۰۰۰

Camera Type

Bullet

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/1.2" Prog. CMOS

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

8MP(3072x1728/20fps)

2MP(1920x1080/25FPS)

4MP(2688 x 1520/25fps)

4MP(2688 x 1520/25fps)

4MP(2688 x 1520/25fps)

6MP(3200 x 1800/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005Lux @ F1.0

0.002 Lux @ F1.4

0.0005 Lux @ F1.0

0.0005 Lux @ F1.0

0.005 Lux @ F1.6

0.005 Lux @ F1.6

Lens

2.8 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

102°

107°

112°

112°

103°/84°

107°/87°

IR Range

Up to 40m (ColorVu)

Up to 30m

Up to 30m (Color Vu)

Up to 30m (Color Vu)

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal / IP67 & IK10

Metal / IP67

Metal / IP67

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

Yes (Up to 256 G)

Yes (Up to 256G)

Microphone Support

Yes (Built in MIC)

Yes (Built in MIC)

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (130db)

Yes (120db)

Yes (130db)

Yes (130db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+ COMP

3D DNR, BLC, HLC, H.265+ COMP, DarkFighter

3D DNR, BLC, HLC, H.265+ COMP

25

26

27

28

29

30

Click for More information

DS-2CD2183G2-IU

DS-2CD2T43G2-2I(4mm)

DS-2CD2T43G2-4I(4mm)

DS-2CD2T63G2-4I

DS-2CD2T83G2-4I

DS-2CD2T86G2-4I



Price (Rials)

۷۴,۲۵۰,۰۰۰

۷۶,۱۴۰,۰۰۰

۷۸,۷۲۴,۱۰۰

۸۰,۸۶۰,۰۰۰

۹۳,۹۰۰,۰۰۰

۱۲۱,۴۴۱,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

8MP(3840 × 2160/25fps)

4MP(2688×1520/25fps)

4MP(2688×1520/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/15fps)

8MP(3840 × 2160/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005 Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.2

0.003Lux @ F1.6

Lens

2.8/4 mm Fixed

4 mm Fixed

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

107°/87°

84°

84°

107°/87°

102°/79°

111°/87°

IR Range

Up to 30m

Up to 60m (EXIR)

Up to 80m (EXIR)

Up to 80m (EXIR)

Up to 80m (EXIR)

Up to 80m (EXIR)

Body Type & Standard

Metal / IP67 & IK10

Metal / IP67

SD Card Support

Yes (Up to 256G)

Microphone Support

Yes (Built in MIC)

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP, ROI3D DNR, BLC, HLC, H.265+
COMP, ROI

31

32

33

34

35

Click for More information

DS-2CD1643G0-IZ

DS-2CD1743G0-IZ

DS-2CD2643G2-IZS

DS-2CD2743G2-IZS

DS-2CD2786G2-IZS



Price (Rials)

۸۱,۳۵۰,۰۰۰

۹۱,۳۴۰,۰۰۰

۱۲۴,۶۶۰,۰۰۰

۱۳۲,۷۶۰,۰۰۰

۱۹۵,۹۷۰,۰۰۰

Camera Type

Bullet

Dome

Bullet

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

4MP(2560 × 1440/20fps)

4MP (2560x1440/20fps)

4MP(2688 × 1520/25fps)

4MP (2560x1440/20FPS)

8MP(3840 × 2160/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.003Lux @ F1.4

Lens

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

102°~31°

91.2°~28.3°

95.8°~29.2°

104°~29°

108°~46°

IR Range

Up to 50m (EXIR)

Up to 30m (EXIR)

Up to 60m

Up to 40m

Up to 40m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP66,IK10

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, H.265+ COMP, Deep Learning

3D DNR, BLC, HLC, H.265+ COMP, Deep Learning, DarkFighter

36

37

Click for More
information

DS-2DE4225IW-DE S6

DS-2DE4425IW-DE T5



Price (Rials)

۲۲۲,۵۱۰,۰۰۰

۲۵۲,۱۰۰,۰۰۰

Camera Type

PTZ

PTZ

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

2MP(1920x1080/60FPS)

4MP(2560 × 1440/30FPS)

Network Standard

ONVIF

ONVIF

Min. Illustration

0.005Lux/F1.6

0.005Lux/F1.6

Lens

4.8-120mm Motorized

4.8-120mm Motorized

Viewing Angle

25x

25x

IR Range

Up to 100m

Up to 100m

Body Type & Standard

Metal/IP66

Metal/IP66

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

WDR

Yes (120db)

Yes (120db)

WIFI

No

No

Power Supply

12 VDC & POE(802.3at)

12 VDC & POE(802.3at)

Other Features

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

38

39

40

41

42

43

Click for More information

DS-7104NI-Q1/M

DS-7108NI-Q1/M

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7608NI-Q2

DS-7608NI-K1



Price (Rials)

٢٢,٣٨٠,٠٠٠

٢٩,٣٨٠,٠٠٠

٦١,٥٦٠,٠٠٠

٨٢,٧٤٠,٠٠٠

٨٠,٠٠٠,٠٠٠

٦٨,٣٤٠,٠٠٠

NVR Type

4 Ch

8 Ch

4 Ch

4 Ch / 4 POE

8 Ch

8 Ch

Input BandWidth

40Mbps

60Mbps

40Mbps

40Mbps

80Mbps

80Mbps

Output Bandwidth

60Mbps

60Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 4k
1 Port VGA : 1080P

POE Ports

-

-

-

4 POE Ports

-

-

SATA Interface

1 HDD up to 6TB

1 HDD up to 6TB

1 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP
Alarm I/O 4/1

44

45

46

47

48

49

Click for More information

DS-7608NI-K1/8P

DS-7616NI-Q2

DS-7716NI-Q4

DS-7716NI-Q4/16P

DS-7616NI-K1

DS-7732NI-K4



Price (Rials)

۱۲۶,۱۹۰,۰۰۰

۸۹,۸۱۰,۰۰۰

۱۷۸,۱۰۰,۰۰۰

۲۵۵,۱۴۰,۰۰۰

۸۵,۸۰۰,۰۰۰

۲۱۰,۳۱۰,۰۰۰

NVR Type

8 Ch / 8 POE

16 Ch

16 Ch

16 Ch / 16 POE

16 Ch

32 Ch

Input BandWidth

80Mbps

160Mbps

160Mbps

160Mbps

160Mbps

256Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

8 POE Ports

-

-

16 POE Ports

-

-

SATA Interface

1 HDD up to 8TB

2 HDD up to 8TB

4 HDD up to 8TB

4 HDD up to 8TB

1 HDD up to 8TB

4 HDD up to 8TB

Network Interface

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

Chassis

Standalone 1U

1U

1.5U

1.5U

Standalone 1U

19" 1.5 Case

Other Features

H.265+ COMP
Alarm I/O 4/1

H.265+ COMP

H.265+ COMP
Alarm I/O 16/4H.265+ COMP
Alarm I/O 16/4

H.265+ COMP

H.265+ COMP
Alarm I/O 16/4

50

51


52

Click for More
information

DS-7732NI-K4/16P

DS-9632NI-I8

IDS-9664NXI-I8/S



Price (Rials)

۳۳۴,۳۱۰,۰۰۰

۷۱۰,۰۰۰,۰۰۰

۷۷۰,۰۰۰,۰۰۰

NVR Type

32 Ch / 16 POE

32 Ch

64 Ch

Input BandWidth

256Mbps

320Mbps

320Mbps

Output Bandwidth

160Mbps

256Mbps

256Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

Decoding Capacity

Upto 8Mp

Upto 12Mp

Upto 12Mp

Video Output

1 Port HDMI : 4K
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P

POE Ports

16 POE Ports

-

-

SATA Interface

4 HDD up to 8TB

8 HDD up to 10TB

8 HDD up to 10TB

Network Interface

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

Chassis

19" 1.5 Case

19" 1.5 Case

2U

Other Features

H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/4, RAIDH.265+ COMPR
Alarm I/O 16/8, RAID,
DeepinMind