



لیست قیمت رسمی مهر ماه ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
Click for More information	DS-2CD1023G0E-I(2.8mm)	DS-2CD1023G0-IUF	DS-2CD1043G0-I(4mm)	DS-2CD1053G0-I	DS-2CD1057G0-L	DS-2CD1123G0E-I
						
Price (Rials)	۲۶,۹۴۰,۰۰۰	۴۰,۷۷۰,۰۰۰	۳۵,۱۶۰,۰۰۰	۵۱,۹۴۰,۰۰۰	۵۸,۸۲۰,۰۰۰	۲۶,۳۶۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Dome
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	2MP(1920x1080/30FPS)	4MP(2560x1440/20fps)	4MP(2560x1440/20fps)	5MP (2560 × 1920/20fps)	2MP(1920x1080/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F1.2
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	112.1°/90.2°	112.1°/90.2°	78.7°	98°	95°/76°	114.8°/86°
IR Range	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 30m	Up to 30m (Color Vu)	Up to 30m
Body Type & Standard	Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Plastic / IP67	Metal / IP67	Plastic / IP67
SD Card Support	No	Yes (Up to 256G)	No	No	Yes (Up to 256G)	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	Yes (120db)	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP

	7	8	9	10	11	12
Click for More information	DS-2CD1143G0-I	DS-2CD1143G0-IUF	DS-2CD1153G0-I(4mm)	DS-2CD1323G0E-I	DS-2CD1347G0-L	DS-2CD1353G0-I (2.8mm)
						
Price (Rials)	۴۱,۷۸۰,۰۰۰	۵۵,۹۶۰,۰۰۰	۵۴,۵۴۰,۰۰۰	۲۹,۵۹۰,۰۰۰	۸۱,۶۵۰,۰۰۰	۵۷,۰۰۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS
Resolution	4MP(2560x1440/20fps)	4MP(2560x1440/20fps)	5MP(2560x1920/15FPS)	2MP(1920x1080/25FPS)	4MP(2560x1440/20fps)	5MP(2560x1920/20FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.028Lux @ F2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F2.0
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed
Viewing Angle	98°/78.7°	98°/78.7°	75.3°	105°/81°	96.5°/75.8°	98.0°
IR Range	Up to 30m	Up to 30m (Color Vu)	Up to 30m	Up to 30m (EXIR)	Up to 30m (Color Vu)	Up to 30m (EXIR)
Body Type & Standard	Plastic / IP67	Plastic / IP67/ IK10	Plastic / IP67/ IK10	Metal/Plastic / IP67	Metal/Plastic / IP67	Metal/Plastic / IP67
SD Card Support	No	Yes (Up to 256 G)	No	No	No	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	DWDR	No	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP

	13	14	15	16	17	18
Click for More information	DS-2CD1357G0-L	DS-2CD2021G1-I (2.8mm)	DS-2CD2023G2-I	DS-2CD2025FHWD-I	DS-2CD2027G2-L (2.8mm)	DS-2CD2043G2-I (2.8mm)
						
Price (Rials)	۵۸,۷۹۰,۰۰۰	۴۹,۹۸۰,۰۰۰	۵۹,۹۴۰,۰۰۰	۶۸,۵۳۰,۰۰۰	۷۱,۰۴۰,۰۰۰	۶۶,۴۶۰,۰۰۰
Camera Type	Dome	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS
Resolution	5MP(2560x1920/20FPS)	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	4MP(2560x1440/30fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.001Lux @ F1.0	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.2	0.005Lux @ F1.6	0.005Lux @ F1.6
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed	2.8 mm Fixed
Viewing Angle	95°/76°	111.6°/91.5°	107°/87°	108°/86.4°	107°	103°
IR Range	Up to 30m (Color Vu)	Up to 30m (EXIR)	Up to 40m	Up to 30m	Up to 40m (Color Vu)	Up to 40m
Body Type & Standard	Metal/Plastic / IP67	Metal/Plastic / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	No	Yes (Up to 256 G)	No	Yes (Up to 128 G)	Yes (Up to 256 G)	Yes (Up to 256 G)
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP

	19	20	21	22	23	24
Click for More information	DS-2CD2043G2-IU(2.8mm)	DS-2CD2046G2-I	DS-2CD2047G2-L	DS-2CD2063G2-I	DS-2CD2066G2-I	DS-2CD2083G2-I
						
Price (Rials)	۷۹,۱۱۰,۰۰۰	۷۰,۷۶۰,۰۰۰	۷۷,۷۳۰,۰۰۰	۷۲,۸۰۰,۰۰۰	۷۸,۳۹۰,۰۰۰	۷۷,۷۱۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/1.8" Prog. CMOS	1/2.4" Prog. CMOS	1/2.4" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	4MP(2560×1440/30fps)	4MP(2688×1520/30fps)	4MP(2560×1440/30fps)	6MP(3200×1800/25fps)	6MP(3200×1800/25fps)	8MP(3840 × 2160/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.6	0.005Lux @ F1.6	0.0005Lux @ F1.0	0.005Lux @ F1.6	0.003Lux @ F1.6	0.005Lux @ F1.6
Lens	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	103°	103°/83°	112°/95°	105°/78°	105°/78°	107°/87°
IR Range	Up to 40m	Up to 40m	Up to 40m (Color Vu)	Up to 40m	Up to 40m	Up to 40m
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 256 G)	Yes (Up to 512 G)	Yes (Up to 256 G)	Yes (Up to 512 G)	Yes (Up to 512 G)	Yes (Up to 512 G)
Microphone Support	Yes (Built in MIC)	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (130db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP

	25	26	27	28	29	30
Click for More information	DS-2CD2085G1-I	DS-2CD2086G2-I	DS-2CD2087G2-LU (2.8mm)	DS-2CD2123G2-IU	DS-2CD2126G2-ISU(2.8mm)	DS-2CD2143G2-IU
						
Price (Rials)	۱۱۷,۱۶۰,۰۰۰	۹۸,۸۱۰,۰۰۰	۱۵۶,۵۵۰,۰۰۰	۶۱,۳۵۰,۰۰۰	۸۱,۵۴۰,۰۰۰	۶۶,۸۹۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Dome	Dome	Dome
Imaging Sensor	1/1.2" Prog. CMOS	1/1.8" Prog. CMOS	1/1.2" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS
Resolution	8MP(3840 × 2160/20fps)	8MP(3840 × 2160/20fps)	8MP(3072×1728/20fps)	4MP(2688 × 1520/25fps)	2MP(1920×1080/25FPS)	4MP(2688 × 1520/25fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.008Lux @ F1.2	0.003Lux @ F1.6	0.0005Lux @ F1.0	0.005 Lux @ F1.6	0.002 Lux @ F1.4	0.005 Lux @ F1.6
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed
Viewing Angle	102°/78°	111°/87°	102°	107°/87°	107°	103°/84°
IR Range	Up to 30m	Up to 40m	Up to 40m (ColorVu)	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10
SD Card Support	Yes (Up to 128 G)	Yes (Up to 256 G)	Yes (Up to 256 G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	No	No	Yes (Built in MIC)	Yes (Built in MIC)	Yes (Built in MIC)	Yes (Built in MIC)
WDR	Yes (120db)	Yes (120db)	Yes (130db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP, DarkFighter	3D DNR, BLC, HLC, H.265+ COMP

	31	32	33	34	35	36
Click for More information	DS-2CD2147G2	DS-2CD2163G2-IU	DS-2CD2166G2-ISU(2.8mm)	DS-2CD2183G2-IU	DS-2CD2185FWD-I	DS-2CD2H25FWD-IZS
						
Price (Rials)	۸۵,۰۰۰,۰۰۰	۷۰,۷۸۰,۰۰۰	۸۳,۴۸۰,۰۰۰	۷۴,۲۸۰,۰۰۰	۱۰۸,۴۶۰,۰۰۰	۱۳۸,۸۷۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/1.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.4" Prog. CMOS	1/2.8" Prog. CMOS	1/2.5" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	4MP(2688 × 1520/25fps)	6MP(3200 × 1800/25fps)	6MP(3200 × 1800/25fps)	8MP(3840 × 2160/25fps)	8MP(3840 × 2160/25fps)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.0005 Lux @ F1.0	0.005 Lux @ F1.6	0.003 Lux @ F1.6	0.005 Lux @ F1.6	0.01 Lux @ F1.2	0.005Lux @ F1.2
Lens	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8-12mm Motorized
Viewing Angle	112°	107°/87°	105°/78°	107°/87°	107°/87°	105°~35°
IR Range	Up to 30m (Color Vu)	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP66/IK10
SD Card Support	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 128G)	Yes (Up to 128 G)
Microphone Support	Yes (Built in MIC)	Yes (Built in MIC)	Yes (Built in MIC)	Yes (Built in MIC)	No	Yes (1.ch Audio Input)
WDR	Yes (130db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, ROI, HLC, H.265+ COMP, DarkFighter

	37	38	39	40	41	42
Click for More information	DS-2CD2327G2-L(2.8)	DS-2CD2347G2-L(2.8mm)	DS-2CD2346G2-IU	DS-2CD2347G2-LU(2.8mm)	DS-2CD2T43G2-2I(2.8)	DS-2CD2T43G2-2I(4mm)
						
Price (Rials)	۸۱,۱۱۰,۰۰۰	۷۸,۹۱۰,۰۰۰	۷۵,۱۳۰,۰۰۰	۸۹,۷۶۰,۰۰۰	۶۶,۹۷۰,۰۰۰	۶۶,۹۷۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Bullet	Bullet
Imaging Sensor	1/2.8" Prog. CMOS	1/1.8" Prog. CMOS	1/3" Prog. CMOS	1/1.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	4MP(2688 × 1520/25fps)	4MP(2688 × 1520/25fps)	4MP(2688 × 1520/25fps)	4MP(2688x1520/25fps)	4MP(2688x1520/25fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.0005 Lux @ F1.0	0.0005 Lux @ F1.0	0.003 Lux @ F1.4	0.0005 Lux @ F1.0	0.005Lux @ F1.6	0.005Lux @ F1.6
Lens	2.8 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed	2.8 mm Fixed	4 mm Fixed
Viewing Angle	107°	112°	103°/83°	112°	103°	84°
IR Range	Up to 30m	Up to 30m (Color Vu)	Up to 30m	Up to 30m (Color Vu)	Up to 60m (EXIR)	Up to 60m (EXIR)
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	No	No	Yes (Built in MIC)	Yes (Built in MIC)	No	No
WDR	Yes (120db)	Yes (130db)	Yes (120db)	Yes (130db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP, DarkFighter	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, HLC, ROI, H.265+ COMP

	43	44	45	46	47	48
Click for More information	DS-2CD2T43G2-4I(4mm)	DS-2CD2T47G-L	DS-2CD2T63G2-4I	DS-2CD2T66G2-4I	DS-2CD2T83G2-4I	DS-2CD2T85G1-I8
						
Price (Rials)	۷۲,۳۸۰,۰۰۰	۹۵,۵۸۰,۰۰۰	۸۰,۸۶۰,۰۰۰	۹۳,۱۸۰,۰۰۰	۹۳,۹۰۰,۰۰۰	۱۳۴,۷۳۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/1.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.4" Prog. CMOS	1/2.5" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	4MP(2688×1520/25fps)	4MP(2688×1520/25fps)	6MP(3200×1800/25fps)	6MP(3200×1800/25fps)	8MP(3840 × 2160/15fps)	8MP(3840 × 2160/15fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.6	0.0005Lux @ F1.0	0.005Lux @ F1.6	0.003Lux @ F1.6	0.005Lux @ F1.2	0.01Lux @ F1.2
Lens	4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	84°	112°/95°	107°/87°	105°/87°	102°/79°	102°/79°
IR Range	Up to 80m (EXIR)	Up to 60m (Color Vu)	Up to 80m (EXIR)	Up to 60m (EXIR)	Up to 80m (EXIR)	Up to 80m
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 256G)	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 512G)	Yes (Up to 256G)	Yes (Up to 128G)
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (130db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP, ROI	3D DNR, BLC, HLC, H.265+ COMP, ROI	3D DNR, BLC, HLC, H.265+ COMP, ROI

	49	50	51	52	53	54
Click for More information	DS-2CD2T86G2-4I	DS-2CD1643G0-IZ	DS-2CD2643G2-IZS	DS-2CD2683G2-IZS	DS-2CD2686G2-IZS	DS-2CD1743G0-IZ
						
Price (Rials)	۱۲۰,۱۵۰,۰۰۰	۸۱,۳۵۰,۰۰۰	۱۲۴,۷۱۰,۰۰۰	۱۳۹,۳۰۰,۰۰۰	۱۷۸,۳۷۰,۰۰۰	۹۱,۳۴۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Dome
Imaging Sensor	1/1.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/2" Prog. CMOS	1/3" Prog. CMOS
Resolution	8MP(3840 × 2160/25fps)	4MP(2560 × 1440/20fps)	4MP(2688 × 1520/25fps)	8MP(3840 × 2160/20fps)	8MP(3840 × 2160/20fps)	4MP (2560x1440/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.003Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.008Lux @ F1.2	0.005Lux @ F1.6
Lens	2.8/4 mm Fixed	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized
Viewing Angle	111°/87°	102°~31°	95.8°~29.2°	108°~30°	112°~46°	91.2°~28.3°
IR Range	Up to 80m (EXIR)	Up to 50m (EXIR)	Up to 60m	Up to 60m	Up to 50m	Up to 30m (EXIR)
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67,IK10	Metal / IP67,IK10	Metal / IP67,IK10	Metal / IP67
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 512G)	Yes (Up to 128G)	Yes (Up to 256G)
Microphone Support	No	No	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC, H.265+ COMP, ROI	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP-	3D DNR, BLC, ROI, H.265+ COMP- DarkFighter	3D DNR, BLC, H.265+ COMP

	55	56	57	58
Click for More information	DS-2CD2743G2-IZS	DS-2CD2783G2-IZS	DS-2CD2785G1-IZS	DS-2CD2443G0-IW(W)
				
Price (Rials)	۱۴۹,۰۰۰,۰۰۰	۱۳۷,۴۷۰,۰۰۰	۱۵۰,۳۲۰,۰۰۰	۶۱,۱۳۰,۰۰۰
Camera Type	Dome	Dome	Dome	Cube
Imaging Sensor	1/3" Prog. CMOS	1/2" Prog. CMOS	1/2" Prog. CMOS	1/3" Prog. CMOS
Resolution	4MP (2560x1440/20FPS)	8MP(3840 × 2160/20fps)	8MP(3840 × 2160/20fps)	4MP (2688x1520/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.6	0.008Lux @ F1.2	0.008Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8/4 mm Fixed
Viewing Angle	104°~29°	112°~46°	112°~46°	98°/78
IR Range	Up to 40m	Up to 30m	Up to 30m	Up to 10m
Body Type & Standard	Metal / IP67,IK10	Metal / IP67,IK10	Metal / IP67,IK10	Plastic
SD Card Support	Yes (Up to 128G)	Yes (Up to 128G)	Yes (Up to 128G)	Yes (Up to 128G)
Microphone Support	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	Yes (Built in MIC)
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, H.265+ COMP, Deep Learning	3D DNR, BLC, ROI, H.265+ COMP- DarkFighter	3D DNR, BLC, ROI, H.265+ COMP- DarkFighter	3D DNR, BLC, HLC, H.265+ COMP, PIR

	59	60	61	62	63	64
Click for More information	DS-2SE4C225MWG-E	DS-2DE4225IW-DE T5	DS-2SE4C425MWG-E	DS-2DE4425IW-DE T5	DS-2DE7A432IW-AEB(T5)	DS-2CD2955FWD-LS
						
Price (Rials)	۲۸۱,۸۱۰,۰۰۰	۲۱۴,۵۹۰,۰۰۰	۳۲۰,۵۶۰,۰۰۰	۲۵۲,۱۵۰,۰۰۰	۴۱۲,۱۷۰,۰۰۰	۱۰۲,۹۶۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	Fisheye
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS(Bullet) 1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/1.8" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	2MP(1920x1080/60FPS)	2MP(1920x1080/60FPS)	4MP(2560x1440/60FPS)	4MP(2560 × 1440/30FPS)	4MP(2560 × 1440/30FPS)	5MP(2560 × 1920/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.0005Lux/F1.0 0.005Lux/F1.6	0.005Lux/F1.6	0.0005Lux/F1.0 0.005Lux/F1.6	0.005Lux/F1.6	0.005Lux/F1.5	0.01Lux/F1.2
Lens	2.8mm (Bullet) 4.8-120mm Motorized	4.8-120mm Motorized	2.8mm (Bullet) 4.8-120mm Motorized	4.8-120mm Motorized	5.9-188.8mm Motorized	1.05mm
Viewing Angle	106°(Bullet) 25x (PTZ)	25x	96.1°(Bullet) 25x (PTZ)	25x	32x	180°
IR Range	Up to 30m(Bullet) Up to 100m	Up to 100m	Up to 30m(Bullet) Up to 100m	Up to 100m	Up to 200m	Up to 8 m
Body Type & Standard	Metal/IP66	Metal/IP66	Metal/IP66	Metal/IP66	Metal/IP66, IK10	Metal
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 128G)
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	24 VAC & Hi-POE	12VDC & POE(802.3at)
Other Features	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR, DarkFighter	3D DNR, H.265+, Anti-flicker

	65	66	67	68	69	70
Click for More information	DS-7104NI-Q1/M	DS-7108NI-Q1/M	DS-7604NI-K1	DS-7604NI-K1/4P	DS-7608NI-Q1	DS-7608NI-K1
						
Price (Rials)	۴۲,۳۸۰,۰۰۰	۴۹,۳۸۰,۰۰۰	۶۱,۵۶۰,۰۰۰	۸۲,۷۴۰,۰۰۰	۵۸,۳۰۰,۰۰۰	۶۸,۳۴۰,۰۰۰
NVR Type	4 Ch	8 Ch	4 Ch	4 Ch / 4 POE	8 Ch	8 Ch
Input BandWidth	40Mbps	60Mbps	40Mbps	40Mbps	80Mbps	80Mbps
Output Bandwidth	60Mbps	60Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 4Mp	Upto 4Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	-	-	4 POE Ports	-	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 8TB	1 HDD up to 8TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP Alarm I/O 4/1

	71	72	73	74	75	76
Click for More information	DS-7608NI-K2	DS-7608NI-K1/8P	DS-7616NI-Q2	DS-7716NI-Q4/16P	DS-7616NI-K1	DS-7616NI-K2
						
Price (Rials)	۷۱,۲۰۰,۰۰۰	۱۲۶,۱۹۰,۰۰۰	۸۹,۸۱۰,۰۰۰	۲۵۵,۱۴۰,۰۰۰	۸۵,۸۰۰,۰۰۰	۸۲,۹۷۰,۰۰۰
NVR Type	8 Ch	8 Ch / 8 POE	16 Ch	16 Ch / 16 POE	16 Ch	16 Ch
Input BandWidth	80Mbps	80Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	8 POE Ports	-	16 POE Ports	-	-
SATA Interface	1 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 8TB	4 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 10TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	1U	1.5U	Standalone 1U	1U
Other Features	H.265+ COMP Alarm I/O 4/1	H.265+ COMP Alarm I/O 4/1	H.265+ COMP	H.265+ COMP Alarm I/O 16/4	H.265+ COMP	H.265+ COMP

	77	78	79	80	81	82
Click for More information	DS-7616NI-K2/16P	DS-7716NI-K4	DS-7732NI-K4	DS-7732NI-K4/16P	IDS-7732NXI-I4/8S	DS-9632NI-I8
						
Price (Rials)	۱۶۲,۳۴۰,۰۰۰	۲۱۱,۱۹۰,۰۰۰	۲۱۰,۴۵۰,۰۰۰	۳۳۴,۳۱۰,۰۰۰	۷۱۹,۱۶۰,۰۰۰	۷۱۰,۰۰۰,۰۰۰
NVR Type	16 Ch / 16 POE	16 Ch	32 Ch	32 Ch / 16 POE	32 Ch	32 Ch
Input BandWidth	160Mbps	160Mbps	256Mbps	256Mbps	320Mbps	320Mbps
Output Bandwidth	160Mbps	160Mbps	160Mbps	160Mbps	256Mbps	256Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 2Ch. Out
Decoding Capacity	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 12Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P
POE Ports	16 POE Ports	-	-	16 POE Ports	-	-
SATA Interface	2 HDD up to 10TB	4 HDD up to 10TB	4 HDD up to 8TB	4 HDD up to 8TB	4 HDD up to 10TB	8 HDD up to 10TB
Network Interface	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Chassis	1U	1.5 U	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case
Other Features	H.265+ COMPR	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/8 - Esata 1- DeepinMind	H.265+ COMPR Alarm I/O 16/4, RAID

	83	84	85
Click for More information	IDS-9632NXI-I8/4F	DS-9632NXI-I8/S	IDS-9664NXI-I8/S



Price (Rials)	۳,۲۱۳,۸۹۰,۰۰۰	۷۳۹,۰۲۰,۰۰۰	۹۶۸,۶۳۰,۰۰۰
NVR Type	32 Ch	32 Ch	64 Ch
Input BandWidth	320Mbps	320Mbps	320Mbps
Output Bandwidth	256Mbps	256Mbps	256Mbps
Audio Input/Output	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out
Decoding Capacity	Upto 12Mp	Upto 12Mp	Upto 12Mp
Video Output	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P
POE Ports	-	-	-
SATA Interface	8 HDD up to 10TB	8 HDD up to 10TB	8 HDD up to 10TB
Network Interface	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Chassis	2U	2U	2U
Other Features	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind



لیست قیمت (رسمی) مهر ماه ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
Click for More information	DS-2CE16D0T-ITPF(2.8mm)	DS-2CE16D0T-ITPFS	DS-2CE16D0T-ITF(3.6mm)	DS-2CE16D0T-ITFS(2.8)	DS-2CE16D0T-ITFS(3.6mm)	DS-2CE16D0T-EXIF
						
Price (Rials)	۱۰,۴۳۰,۰۰۰	۱۶,۳۹۰,۰۰۰	۱۳,۸۳۰,۰۰۰	۱۷,۶۲۰,۰۰۰	۱۷,۴۱۰,۰۰۰	۱۲,۹۸۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.02Lux/F1.2
Lens	2.8mm Fixed	2.8/3.6/6mm Fixed	2.8/3.6mm Fixed	2.8mm Fixed	3.6mm Fixed	2.8/3.6mm Fixed
Viewing Angle	106.4°	106.4°/79.6° /51.9°	101°/79.6°	106.4°	79.6°	102°/81°
IR Range	Up to 25m	Up to 25m (Exir)	Up to 30m (Exir)	Up to 30m (Exir)	Up to 30m (Exir)	Up to 20m
Body Type	Plastic	Plastic	Metal	Metal	Metal	Metal
IP Standard	IP67	IP67	IP67	IP67	IP67	IP66
OSD Menu	No	No	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, HLC, DNR, BLC, 2D DNR, Switchable	Smart IR, Switchable, Built in mic	Smart IR, HLC, DNR, BLC, 2D DNR, Switchable	HLC,2D DNR, BLC, Switchable, Built-in microphone	HLC,2D DNR, BLC, Switchable, Built-in microphone	2D DNR, BLC, Switchable

	7	8	9	10	11	12
Click for More information	DS-2CE16D0T-EXIPF	DS-2CE16D3T-ITF	DS-2CE16D3T-IT3F(2.8mm)	DS-2CE17D0T-IT1F	DS-2CE17D0T-IT3F(2.8mm)	DS-2CE10DF0T-F
						
Price (Rials)	۱۲,۴۰۰,۰۰۰	۲۱,۶۶۰,۰۰۰	۲۲,۲۴۰,۰۰۰	۱۸,۰۵۰,۰۰۰	۲۳,۱۶۰,۰۰۰	۳۲,۱۳۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.02Lux/F1.2	0.02Lux/F1.2	0.005Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.001Lux/F1.0
Lens	2.8/3.6mm Fixed	2.8/3.6mm Fixed	2.8mm Fixed	2.8/3.6mm Fixed	2.8mm Fixed	2.8/3.6mm Fixed
Viewing Angle	96.5°/76.9°	106°/82°	106°	101°/79.6°	106.4°	98°/76°
IR Range	Up to 20m (Exir)	Up to 30m (Exir)	Up to 50m (Exir)	Up to 30m (Exir)	Up to 40m	Up to 20m
Body Type	Plastic	Metal	Metal	Metal & Plastic	Metal & Plastic	Metal
IP Standard	IP66	IP67	IP67	IP67	IP67	IP67
OSD Menu	No	No	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	DWDR	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	2D DNR, BLC, AGC, Switchable	3D DNR,HLC, BLC, Switchable	3D DNR,HLC, BLC, Switchable	3D DNR,HLC, BLC, AGC, Switchable	HLC, BLC, AGC, Switchable	HLC, BLC, AGC, Switchable

13

14

15

16

17

18

Click for More
information

DS-2CE10DF3T-F(3.6mm)

DS-2CE10DF3T-FS(2.8mm)

DS-2CE12DF3T-F(3.6mm)

DS-2CE12DF3T-FS(2.8mm)

DS-2CE76D0T-ITPF(C)(2.8)

DS-2CE76D0T-EXIPF(2.8mm)



Price (Rials)	۲۳,۷۶۰,۰۰۰	۲۴,۰۷۰,۰۰۰	۲۳,۴۷۰,۰۰۰	۲۸,۳۳۰,۰۰۰	۱۱,۲۵۰,۰۰۰	۱۳,۳۹۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.0005Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01Lux/F1.2	0.01Lux/F1.2
Lens	3.6mm Fixed	2.8mm Fixed	3.6mm Fixed	2.8mm Fixed	2.8mm Fixed	2.8mm Fixed
Viewing Angle	77°	98°	77°	98°	103°	96.5°
IR Range	Up to 20m (ColorVu)	Up to 20m (ColorVu)	Up to 40m (ColorVu)	Up to 40m (ColorVu)	Up to 20m (Exir)	Up to 20m (Exir)
Body Type	Metal	Metal	Metal	Metal	Plastic	Plastic
IP Standard	IP67	IP67	IP67	IP67	IP66	IP66
OSD Menu	No	No	No	No	No	No
WDR	Yes (130db)	Yes (130db)	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	HLC, BLC, Smart IR, Switchable, 3D DNR	HLC, BLC, Smart IR, Switchable, 3D DNR, Built in mic	HLC, BLC, Smart IR, Switchable, 3D DNR	HLC, BLC, Smart IR, Switchable, 3D DNR, Built in mic	Smart IR, HLC,BLC, Switchable	Smart IR, HLC,BLC, Switchable

	19	20	21	22	23	24
Click for More information	DS-2CE76D0T-ITPFS	DS-2CE76D0T-ITMF(2.8)	DS-2CE76D0T-ITMFS(2.8)	DS-2CE76D3T-ITPF	DS-2CE76D3T-ITMF(2.8mm)	DS-2CE56D0T-VFIR3F
						
Price (Rials)	۱۴,۸۴۰,۰۰۰	۱۶,۴۴۰,۰۰۰	۱۸,۸۱۰,۰۰۰	۱۷,۴۲۰,۰۰۰	۲۳,۸۴۰,۰۰۰	۳۲,۲۴۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2	0.005Lux/F1.2	0.005Lux/F1.2	0.01Lux/F1.2
Lens	2.8/3.6/6mm Fixed	2.8mm Fixed	2.8mm Fixed	2.8/3.6/6mm Fixed	2.8mm Fixed	2.8 - 12mm VariFocal
Viewing Angle	106°/79.6°/51°	101°	106.4°	106°/82° /51°	106°	105°/ 32°
IR Range	Up to 20m (Exir)	Up to 30m	Up to 30m (Exir)	Up to 30m(Exir)	Up to 30m(Exir)	Up to 40m
Body Type	Plastic	Metal	Metal	Plastic	Metal	Metal & Plastic
IP Standard	IP66	IP67	IP67	IP66	IP67	IP66
OSD Menu	No	No	No	Yes	No	No
WDR	DWDR	DWDR	DWDR	Yes (120db)	Yes (120db)	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, HLC,BLC, Switchable	Smart IR, ICR, HLC,BLC, 2D DNR, Switchable	ICR,AGC, Switchable, Built in mic	Smart IR, HLC,BLC, Switchable	Smart IR, HLC,BLC, Switchable, 3D DNR	Smart IR, ICR, AGC, Switchable

	25	26	27	28	29	30
Click for More information	DS-2CE78D0T-IT3FS	DS-2CE70DF0T-PF	DS-2CE70DF3T-PF(3.6mm)	DS-2CE72DF3T-F(3.6)	DS-2CE16H0T-ITPF	DS-2CE16H0T-ITPFS(2.8)
						
Price (Rials)	۲۳,۸۴۰,۰۰۰	۳۴,۷۲۰,۰۰۰	۲۶,۹۸۰,۰۰۰	۲۵,۴۱۰,۰۰۰	۱۷,۷۴۰,۰۰۰	۲۰,۷۷۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Bullet	Bullet
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	5 Megapixel	5 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	5MP (2560*1944)	5MP (2592*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F2.0	0.001Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01Lux/F1.2	0.01Lux/F1.2
Lens	2.8/3.6/6mm Fixed	2.8/3.6/6mm Fixed	3.6mm Fixed	3.6mm Fixed	2.8/3.6/6mm Fixed	2.8mm Fixed
Viewing Angle	98°/76°/50°	98°/76°/50°	77°	77°	85.5°/80.1°/57.1°	85.5°
IR Range	Up to 40m (Exir)	Up to 20m (ColorVu)	Up to 20m (ColorVu)	Up to 40m (ColorVu)	Up to 20m (Exir)	Up to 25m (Exir)
Body Type	Plastic	Plastic	Plastic	Metal & Plastic	Plastic	Plastic
IP Standard	IP67	IP66	IP66	IP67	IP67	IP67
OSD Menu	No	No	No	No	No	No
WDR	DWDR	DWDR	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	AGC, Switchable, Built in Mic	AGC, Switchable	AGC, Switchable, 3D DNR	AGC, Switchable, 3D DNR	Smart IR, BLC,AGC, DNR, Switchable	Smart IR, HLC,BLC,AGC, 2D DNR, Switchable, Built in Mic

	31	32	33	34	35	36
Click for More information	DS-2CE16H0T-ITPFS(3.6mm)	DS-2CE16H0T-ITF(3.6mm)	DS-2CE16H0T-ITFS	DS-2CE17H0T-IT1F	DS-2CE17H0T-IT3F(2.8mm)	DS-2CE17H0T-IT3F(3.6mm)
						
Price (Rials)	۲۱,۴۲۰,۰۰۰	۱۹,۴۷۰,۰۰۰	۲۳,۰۵۰,۰۰۰	۲۳,۲۳۰,۰۰۰	۲۳,۲۰۰,۰۰۰	۲۴,۱۰۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel
Resolution	5MP (2592*1944)	5MP (2592*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1	0.01Lux/F1	0.01Lux/F1.2	0.01Lux/F1.2	0.01Lux/F1.2
Lens	2.8/3.6mm Fixed	2.8/3.6mm Fixed	2.8/3.6/6mm Fixed	2.4/2.8/3.6mm Fixed	2.8mm Fixed	3.6mm Fixed
Viewing Angle	85.5°/80.1°	85.5°/80.1°	85.5°/80.1°/57.1°	110°/85°/80°	85°	80°
IR Range	Up to 25m (Exir)	Up to 20m (Exir)	Up to 30m (Exir)	Up to 30m	Up to 40m	Up to 40m
Body Type	Plastic	Metal	Metal	Metal & Plastic	Metal & Plastic	Metal & Plastic
IP Standard	IP67	IP67	IP67	IP67	IP67	IP67
OSD Menu	No	Yes	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, HLC,BLC,AGC, 2D DNR, Switchable, Built in Mic	2D DNR, DWDR, Switchable	2D DNR, Switchable, Built in Mic	Smart IR, 2D DNR, HLC,BLC, Switchable	Smart IR, 2D DNR, HLC,BLC, Switchable	Smart IR, 2D DNR, HLC,BLC, Switchable

	37	38	39	40	41	42
Click for More information	DS-2CE17H0T-IT3FS(2.8mm) DS-2CE17H0T-IT5F(3.6mm) DS-2CE12HFT-F(3.6mm) DS-2CE10HFT-F(3.6mm) DS-2CE56H0T-IT1F DS-2CE76H0T-ITPF(2.4mm)					
						
Price (Rials)	۲۹,۷۹۰,۰۰۰	۲۴,۴۶۰,۰۰۰	۴۰,۱۶۰,۰۰۰	۳۴,۸۱۰,۰۰۰	۲۰,۹۰۰,۰۰۰	۱۷,۴۱۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Imaging Sensor	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel
Resolution	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1.2	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01 Lux/F1.2	0.01 Lux/F1.2
Lens	2.8mm Fixed	3.6/6/8mm Fixed	3.6/6mm Fixed	3.6/6mm Fixed	2.8/3.6/6mm Fixed	2.4mm Fixed
Viewing Angle	85°	80°/57°/41°	80.0°/49.3°	80.0°/49.3°	105°/85°/65°	110°
IR Range	Up to 40m	Up to 80m	Up to 40m	Up to 20m	Up to 20m (Exir)	Up to 20m (Exir)
Body Type	Metal & Plastic	Metal & Plastic	Metal	Metal	Metal & Plastic	Plastic
IP Standard	IP67	IP67	IP67	IP67	IP67	IP67
OSD Menu	No	No	No	No	Yes	No
WDR	DWDR	DWDR	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, 2D DNR, HLC,BLC, Switchable, Built in mic	Smart IR, 2D DNR, HLC,BLC, Switchable	Smart IR, 3D DNR, HLC,BLC,HLS,Anti-banding, Switchable	Smart IR, 3D DNR, HLC,BLC,HLS,Anti-banding, Switchable	Smart IR, ICR, AGC, BLC, Switchable	Smart IR, ICR, AGC, BLC, HLC

43

44

45

46

47

48

[Click for More information](#)

DS-2CE76H0T-ITPF(2.8mm)

DS-2CE76H0T-ITMF(2.8)

DS-2CE76H0T-ITMFS(2.8)

DS-2CE78H0T-IT1F(2.4mm)

DS-2CE78H0T-IT3F

DS-2CE78H0T-IT3FS(3.6mm)



Price (Rials)

۱۶,۳۰۰,۰۰۰

۲۱,۴۴۰,۰۰۰

۲۴,۲۹۰,۰۰۰

۲۳,۸۶۰,۰۰۰

۲۵,۷۹۰,۰۰۰

۲۴,۳۰۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

Resolution

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

5MP (2560*1944)

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F1.2

0.01 Lux/F2.0

Lens

2.8mm Fixed

2.8mm Fixed

2.8mm Fixed

2.4 mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6/6mm Fixed

Viewing Angle

85°

105°

85°

110°

85°/80°/57°

85.5°/80°/57°

IR Range

Up to 20m (Exir)

Up to 30m (Exir)

Up to 30m

Up to 30m (Exir)

Up to 40m (Exir)

Up to 40m

Body Type

Plastic

Metal

Metal

Metal & Plastic

Metal & Plastic

Metal & Plastic

IP Standard

IP67

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, ICR, AGC, BLC, HLC

Smart IR, ICR, AGC, BLC, Switchable

Smart IR, ICR, AGC, BLC, Switchable, Built in mic

Smart IR, ICR, AGC, BLC,HLC, Switchable

Smart IR, ICR, AGC,HLC, BLC, Switchable

Smart IR, ICR, AGC, Switchable, Built in mic

49

50

51

52

Click for More
information

DS-2CE72HFT-F28(2.8mm)

DS-2CE72KF0T-FS(2.8mm)

DS-2CE78U8T-IT3

DS-2AE4225TI-D



Price (Rials)

۳۸,۳۷۰,۰۰۰

۳۷,۴۰۰,۰۰۰

۶۳,۸۷۰,۰۰۰

۱۸۰,۵۲۰,۰۰۰

Camera Type

Dome

Dome

Dome

PTZ

Imaging Sensor

5 Megapixel

3K

8.29 Megapixel

2 Megapixel

Resolution

5MP (2560*1944)

3K (2960*1665)

8MP (3840*2160)

1920 × 1080

Signal System

HD-TVI

HD-TVI

HD-TVI

HD-TVI

Min. Illustration

0.0005 Lux/F1.0

0.001 Lux/F1.0

0.003 Lux/F1.2

0.005 Lux/F1.6

Lens

2.8mm Fixed

2.8mm Fixed

2.8/3.6/6mm Fixed

4.8 mm-120mm

Viewing Angle

99.7°

102°

105°/85°/65°

25x Optical Zoom

IR Range

Up to 20m (ColorVu)

Up to 40m (ColorVu)

Up to 60m (Exir)

Up to 100m

Body Type

Metal & Plastic

Metal & Plastic

Metal & Plastic

Metal

IP Standard

IP67

IP67

IP67

IP66

OSD Menu

No

No

No

No

WDR

Yes (130db)

DWDR

Yes (120db)

Yes (120db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, 3D DNR

Smart IR, 3D DNR, Built in mic

Smart IR, ICR

Smart IR, ICR, Switchable, DarkFighter

	53	54	55	56	57	58
Click for More information	DS-7216HGHI-K1	IDS-7204HQHI-M1/S	IDS-7208HQHI-M1/S	DS-7216HQHI-K1	DS-7216HQHI-M1/S	IDS-7216HQHI-M2/S
						
Price (Rials)	۷۲,۲۷۰,۰۰۰	۴۶,۵۲۰,۰۰۰	۷۱,۲۹۰,۰۰۰	۱۲۱,۸۰۰,۰۰۰	۱۲۴,۰۹۰,۰۰۰	۱۵۱,۱۵۰,۰۰۰
DVR Type	16+2 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP	4+1 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP	8+2 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP	16+2 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP	16+2 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP	16+2 Ch. quadruple Hybrid HD-TVI /AHD/ Analog / IP
Analog Video Input	16 Ch. HDTVI/Analog Up to 2MP	4 Ch. HDTVI/Analog Up to 4MP	8 Ch. HDTVI/Analog Up to 4MP	16 Ch. HDTVI/Analog Up to 4MP	16 Ch. HDTVI/Analog Up to 4MP	16 Ch. HDTVI/Analog Up to 4MP
IP Video Input	2 Ch. Up to 5MP	1 Ch. Up to 6MP	2 Ch. Up to 6MP	2 Ch. Up to 6MP	2 Ch. Up to 6MP	2 Ch. Up to 6MP
Audio Input/Output	1Ch. In / 1Ch. Out	1Ch. In / 1Ch. Out	1Ch. In / 1Ch. Out	1Ch. In / 1Ch. Out	1Ch. In / 1Ch. Out	1Ch. In / 1Ch. Out
Recording	1080P: 15FPS 720P: 15FPS VGA: 25FPS	4MP: 15FPS 3MP: 15FPS 1080P: 15FPS	4MP: 15FPS 3MP: 15FPS 1080P: 15FPS	4MP: 15FPS 3MP: 15FPS 1080P: 15FPS	3K: 30FPS 5MP: 20FPS 1080P: 30FPS	4MP: 15FPS 3MP: 15FPS 1080P: 15FPS
Video Output	1 Port HDMI : 1080P 1 Port VGA	1 Port HDMI 1080P 1 Port VGA, 1Ch. CVBS	1 Port HDMI 1080P 1 Port VGA, 1Ch. CVBS	1 Port HDMI : 4K 1 Port VGA 1Ch. CVBS	1 Port HDMI : 4K 1 Port VGA 1Ch. CVBS	1 Port HDMI 1080P 1 Port VGA 1Ch. CVBS
SATA Interface	1 HDD up to 10TB	1 HDD up to 10TB	1 HDD up to 10TB	1 HDD up to 10TB	1 HDD up to 10TB	2 HDD up to 10TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.265/H.265 pro+ Compression, ONVIF, Deep learning	H.265/H.265+ Compression, ONVIF, Smart Search	H.265/H.265+ Compression, ONVIF, Smart Search	H.265/H.265+ Compression, ONVIF, VCA, Smart Search	H.265/H.265 pro+ Compression, ONVIF, VCA, Smart Search	H.265/H.265+ Compression, ONVIF, VCA, Smart Search

59

60

61

62

63

64

[Click for More information](#)

iDS-7232HQHI-K2

iDS-7232HQHI-M2/S

DS-7204HUHI-K1

DS-7204HUHI-K1/P

DS-7204HUHI-M1/S

DS-7208HUHI-M1/S



Price (Rials)

۲۶۷,۳۲۰,۰۰۰

۲۴۸,۳۱۰,۰۰۰

۶۷,۷۲۰,۰۰۰

۶۷,۴۷۰,۰۰۰

۷۴,۷۲۰,۰۰۰

۱۲۰,۶۱۰,۰۰۰

DVR Type

32+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP32+2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4 +2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4 +2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP4 + 2 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP8 + 4 Ch. quadruple Hybrid
HD-TVI /AHD/ Analog / IP

Analog Video Input

32 Ch. HDTV/Analog
Up to 4MP32 Ch. HDTV/Analog
Up to 4MPSupport
Up to 5MP resolution
recordingSupport
Up to 5MP resolution
recordingSupport
Up to 5MP resolution
recordingSupport
Up to 5MP resolution
recording

IP Video Input

2 Ch. Up to 6MP

2 Ch. Up to 6MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

4 Ch. Up to 8MP

Audio Input/Output

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

Recording

4MP: 15FPS
3MP: 15FPS
1080P: 15FPS4MP: 15FPS
3MP: 15FPS
1080P: 15FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 12FPS
4MP: 15FPS
3mp: 18FPS5MP: 30FPS
4MP: 30FPS
3mp: 30FPS

Video Output

1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS1 Port HDMI : 4K
1 Port VGA
1Ch. CVBS1 Port HDMI : 1080P
1 Port VGA1 Port HDMI : 1080P
1 Port VGA
CVBS: PAL1 Port HDMI : 2K
1 Port VGA
CVBS: PAL1 Port HDMI : 4K
1 Port VGA

SATA Interface

2 HDD up to 10TB

2 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265 Pro+/H.265
Pro/H.265/ Compression,
VCAH.265/H.265+
Compression, ONVIF,
VCA, Smart SearchH.265/H.265+ COMPR
Alarm In/Out : 4/1
Onvif, VCAH.265/H.265+ COMPR
Alarm In/Out : 4/1
Built-in PoCH.265/H.265+ COMPR
Alarm In/Out : N/AH.265 Pro+/H.265 Pro,
Onvif

65

66

67

Click for More
information

DS-7216HUHI-K2

IDS-7216HUHI-M2/S

DS-7316HUHI-F4/N



Price (Rials)

۲۱۸,۷۳۰,۰۰۰

۲۲۴,۰۹۰,۰۰۰

۴۴۷,۲۷۰,۰۰۰

DVR Type

16+16Ch.quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+8 Ch.quadruple Hybrid
HD-TVI /AHD/ Analog / IP16+2 Ch.quadruple Hybrid
HD-TVI /AHD/ Analog / IP

Analog Video Input

Support
Up to 5MP resolution
recordingSupport
Up to 5MP resolution
recordingSupport
Up to 3MP resolution
recording

IP Video Input

16 Ch. Up to 8MP

8 Ch. Up to 8MP

2 Ch. Up to 8MP

Audio Input/Output

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

Recording

5MP: 20FPS
4MP: 25FPS
3mp: 18FPS5MP: 20FPS
4MP: 25FPS
3mp: 18FPS3mp: 15FPS
2mp: 25FPS
720p: 25FPS

Video Output

1 Port HDMI : 4K
1 Port VGA
CVBS: PAL1 Port HDMI : 4K
1 Port VGA
CVBS: PAL2 Port HDMI : 4K/1080p
1 Port VGA
CVBS: PAL

SATA Interface

2 HDD up to 10TB

2 HDD up to 10TB

4 HDD up to 6TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265/H.265+ COMPR
Alarm In/Out : 16/4H.265/H.265+ COMPR
Alarm In/Out : N/AH.265/H.265+ COMPR
Alarm In/Out : N/A