

HIKVISION

لیست قیمت رسمی دی ماه ۱۴۰۲








تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
Click for More information	DS-2CD1023G0E-I(2.8mm)	DS-2CD1023G0-IUF	DS-2CD1043G0-I	DS-2CD1053G0-I(4mm)	DS-2CD1057G0-L	DS-2CD1123G0E-I
						
Price (Rials)	۲۶,۹۴۰,۰۰۰	۴۰,۷۷۰,۰۰۰	۳۵,۱۶۰,۰۰۰	۵۱,۹۴۰,۰۰۰	۵۸,۸۲۰,۰۰۰	۲۶,۳۶۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Dome
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	2MP(1920x1080/30FPS)	4MP(2560x1440/20fps)	5MP (2560 × 1920/20fps)	5MP (2560 × 1920/20fps)	2MP(1920x1080/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F1.2
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	112.1°/90.2°	112.1°/90.2°	98.0°/78.7°	78.7°	95°/76°	114.8°/86°
IR Range	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 30m	Up to 30m (Color Vu)	Up to 30m
Body Type & Standard	Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Plastic / IP67	Metal / IP67	Plastic / IP67
SD Card Support	No	Yes (Up to 256G)	No	No	Yes (Up to 256G)	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	Yes (120db)	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP

7

8

9

10

11

12

Click for More
information

DS-2CD1143G0-I

DS-2CD1143G0-IUF

DS-2CD1153G0-I(4mm)

DS-2CD1323G0E-I

DS-2CD1347G0-L

DS-2CD1353G0-I (2.8mm)



Price (Rials)

۴۱,۷۸۰,۰۰۰

۴۵,۴۴۰,۰۰۰

۵۴,۵۴۰,۰۰۰

۲۹,۵۹۰,۰۰۰

۸۱,۶۵۰,۰۰۰

۵۷,۰۰۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

4MP(2560x1440/20fps)

4MP(2560x1440/20fps)

5MP(2560x1920/15FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/20fps)

5MP(2560x1920/20FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.028Lux @ F2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.01Lux @ F2.0

0.001Lux @ F1.0

0.01Lux @ F2.0

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

Viewing Angle

98°/78.7°

98°/78.7°

75.3°

105°/81°

96.5°/75.8°

98.0°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m (EXIR)

Up to 30m (Color Vu)

Up to 30m (EXIR)

Body Type & Standard

Plastic / IP67

Plastic / IP67/ IK10

Plastic / IP67/ IK10

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256 G)

No

No

No

No

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

DWDR

Yes (120db)

Yes (120db)

DWDR

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,
H.265+ COMP3D DNR, BLC, ROI, VCA,
H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP

13

14

15

16

17

18

Click for More
information

DS-2CD1357G0-L

DS-2CD2021G1-I (2.8mm)

DS-2CD2023G2-I

DS-2CD2025FHWD-I

DS-2CD2027G2-L (2.8mm)

DS-2CD2043G2-I (2.8mm)



Price (Rials)

۵۸,۷۹۰,۰۰۰

۴۹,۹۸۰,۰۰۰

۶۱,۲۴۰,۰۰۰

۷۰,۰۶۰,۰۰۰

۷۱,۰۴۰,۰۰۰

۶۶,۵۶۰,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

Resolution

5MP(2560x1920/20FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/30fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.001Lux @ F1.0

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

Viewing Angle

95°/76°

111.6°/91.5°

107°/87°

108°/86.4°

107°

103°

IR Range

Up to 30m (Color Vu)

Up to 30m (EXIR)

Up to 40m

Up to 30m

Up to 40m (Color Vu)

Up to 40m

Body Type & Standard

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

No

Yes (Up to 256 G)

No

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+
COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP

19

20

21

22

23

24

Click for More
information

DS-2CD2043G2-I(4mm)

DS-2CD2043G2-IU(2.8mm)

DS-2CD2046G2-I(2.8mm)

DS-2CD2047G2-L

DS-2CD2063G2-I

DS-2CD2066G2-I(2.8mm)



Price (Rials)

٤٦,٥٦٠,٠٠٠

٧٩,١١٠,٠٠٠

٧٢,٣٧٠,٠٠٠

٧٧,٧٣٠,٠٠٠

٧٣,٠٥٠,٠٠٠

٨٠,٢٢٠,٠٠٠

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.4" Prog. CMOS

Resolution

4MP(2560×1440/30fps)

4MP(2560×1440/30fps)

4MP(2688×1520/30fps)

4MP(2560×1440/30fps)

6MP(3200×1800/25fps)

6MP(3200×1800/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

0.003Lux @ F1.6

Lens

4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

Viewing Angle

84°

103°

103°

112°/95°

105°/78°

105°

IR Range

Up to 40m

Up to 40m

Up to 40m

Up to 40m (Color Vu)

Up to 40m

Up to 40m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 512 G)

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP

25

26

27

28

29

30

Click for More
information

DS-2CD2083G2-I

DS-2CD2085G1-I

DS-2CD2086G2-I(2.8mm)

DS-2CD2087G2-LU (2.8mm)

DS-2CD2123G2-IU

DS-2CD2126G2-ISU(2.8mm)



Price (Rials)

۷۹,۱۹۰,۰۰۰

۱۱۷,۱۶۰,۰۰۰

۱۰۱,۰۴۰,۰۰۰

۱۵۶,۵۵۰,۰۰۰

۶۲,۸۱۰,۰۰۰

۸۱,۵۴۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Dome

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/1.2" Prog. CMOS

1/1.8" Prog. CMOS

1/1.2" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

8MP(3072×1728/20fps)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.008Lux @ F1.2

0.003Lux @ F1.6

0.0005Lux @ F1.0

0.005 Lux @ F1.6

0.002 Lux @ F1.4

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

Viewing Angle

107°/87°

102°/78°

111°

102°

107°/87°

107°

IR Range

Up to 40m

Up to 30m

Up to 40m

Up to 40m (ColorVu)

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

Yes (Up to 512 G)

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP, DarkFighter

31

32

33

34

35

36

Click for More
information

DS-2CD2143G2-IU

DS-2CD2147G2

DS-2CD2163G2-IU

DS-2CD2166G2-ISU(2.8mm)

DS-2CD2183G2-IU

DS-2CD2185FWD-I



Price (Rials)

۶۶,۸۹۰,۰۰۰

۸۶,۹۸۰,۰۰۰

۷۱,۹۲۰,۰۰۰

۸۷,۳۹۰,۰۰۰

۷۴,۲۸۰,۰۰۰

۱۰۸,۴۶۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

6MP(3200 × 1800/25fps)

6MP(3200 × 1800/25fps)

8MP(3840 × 2160/25fps)

8MP(3840 × 2160/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005 Lux @ F1.6

0.0005 Lux @ F1.0

0.005 Lux @ F1.6

0.003 Lux @ F1.6

0.005 Lux @ F1.6

0.01 Lux @ F1.2

Lens

2.8/4 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

103°/84°

112°

107°/87°

105°/78°

107°/87°

107°/87°

IR Range

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 128G)

Microphone Support

Yes (Built in MIC)

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

No

WDR

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP

37

38

39

40

41

42

Click for More
information

DS-2CD2186G2-ISU

DS-2CD2H25FWD-IZS

DS-2CD2327G2-L(2.8)

DS-2CD2347G2-L(2.8mm)

DS-2CD2346G2-IU(2.8mm)

DS-2CD2347G2-LU(2.8mm)



Price (Rials)

۱۸۱,۵۹۰,۰۰۰

۱۳۸,۸۷۰,۰۰۰

۸۱,۱۱۰,۰۰۰

۷۸,۹۱۰,۰۰۰

۷۶,۸۲۰,۰۰۰

۸۹,۷۶۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

8MP(3840 × 2160/25fps)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.003 Lux @ F1.6

0.005Lux @ F1.2

0.0005 Lux @ F1.0

0.0005 Lux @ F1.0

0.003 Lux @ F1.4

0.0005 Lux @ F1.0

Lens

2.8/4 mm Fixed

2.8-12mm Motorized

2.8 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

Viewing Angle

111°/87°

105°~35°

107°

112°

103°

112°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (Color Vu)

Body Type & Standard

Metal / IP67 & IK10

Metal / IP66/IK10

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 128 G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Microphone Support

Yes (Built in MIC)

Yes (1.ch Audio Input)

No

No

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (130db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, ROI, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP, DarkFighter3D DNR, BLC, HLC,H.265+
COMP

43

44

45

46

47

48

Click for More
information

DS-2CD1T43G2-LIU(4mm)

DS-2CD2T43G2-2I(2.8mm)

DS-2CD2T43G2-2I(4mm)

DS-2CD2T43G2-4I(4mm)

DS-2CD2T47G-L

DS-2CD2T63G2-4I



Price (Rials)

۴۸,۰۱۰,۰۰۰

۶۶,۹۷۰,۰۰۰

۶۶,۹۷۰,۰۰۰

۷۲,۳۸۰,۰۰۰

۹۵,۵۸۰,۰۰۰

۸۲,۳۳۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP (2560x1440/20fps)

4MP(2688x1520/25fps)

4MP(2688x1520/25fps)

4MP(2688x1520/25fps)

4MP(2688x1520/25fps)

6MP(3200x1800/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

Lens

4 mm Fixed

2.8 mm Fixed

4 mm Fixed

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

78°

103°

84°

84°

112°/95°

107°/87°

IR Range

Up to 50m (Hybrid Light)

Up to 60m (EXIR)

Up to 60m (EXIR)

Up to 80m (EXIR)

Up to 60m (Color Vu)

Up to 80m (EXIR)

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Microphone Support

Yes (Built in MIC)

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP

49

50

51

52

53

54

Click for More
information

DS-2CD2T66G2-4I(4mm)

DS-2CD2T83G2-4I

DS-2CD2T85G1-I5

DS-2CD2T85G1-I8

DS-2CD2T86G2-4I(4mm)

DS-2CD2T87G2-L(2.8mm)



Price (Rials)

۹۴,۲۱۰,۰۰۰

۹۳,۹۰۰,۰۰۰

۱۰۴,۲۶۰,۰۰۰

۱۳۴,۷۳۰,۰۰۰

۱۲۰,۱۵۰,۰۰۰

۲۰۰,۶۸۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.4" Prog. CMOS

1/2.5" Prog. CMOS

1/2" Prog. CMOS

1/2.5" Prog. CMOS

1/1.8" Prog. CMOS

1/1.2" Prog. CMOS

Resolution

6MP(3200x1800/25fps)

8MP(3840 x 2160/15fps)

8MP(3840 x 2160/20fps)

8MP(3840 x 2160/15fps)

8MP(3840 x 2160/25fps)

8MP(3840 x 2160/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.003Lux @ F1.6

0.005Lux @ F1.2

0.008Lux @ F1.2

0.01Lux @ F1.2

0.003Lux @ F1.6

0.0005Lux @ F1.6

Lens

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

87°

102°/79°

110.7°/87.1°

110.7°/87.1°

111°/87°

102°/88°

IR Range

Up to 60m (EXIR)

Up to 80m (EXIR)

Up to 50m

Up to 80m

Up to 80m (EXIR)

Up to 60m (Color Vu)

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+
COMP, ROI3D DNR, BLC, HLC,H.265+
COMP, ROI3D DNR, BLC, HLC,H.265+
COMP, ROI3D DNR, BLC, HLC,H.265+
COMP, ROI3D DNR, BLC, HLC,H.265+
COMP, ROI3D DNR, BLC, HLC,H.265+
COMP, ROI

55

56

57

58

59

60

Click for More
information

DS-2CD1643G0-IZ

DS-2CD2643G2-IZS

DS-2CD2666G2-IZS

DS-2CD2683G2-IZS

DS-2CD2686G2-IZS

DS-2CD1743G0-IZ



Price (Rials)

۷۵,۰۳۰,۰۰۰

۱۲۴,۷۱۰,۰۰۰

۱۵۲,۶۴۰,۰۰۰

۱۴۲,۶۸۰,۰۰۰

۱۸۱,۵۹۰,۰۰۰

۹۱,۳۴۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

1/2" Prog. CMOS

1/3" Prog. CMOS

Resolution

4MP(2560 × 1440/20fps)

4MP(2688 × 1520/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2560x1440/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0035Lux @ F1.4

0.005Lux @ F1.6

0.008Lux @ F1.2

0.005Lux @ F1.6

Lens

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

102°~31°

95.8°~29.2°

106°~35°

108°~30°

112°~46°

91.2°~28.3°

IR Range

Up to 50m (EXIR)

Up to 60m

Up to 60m

Up to 60m

Up to 50m

Up to 30m (EXIR)

Body Type & Standard

Metal / IP67

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 512G)

Yes (Up to 128G)

Yes (Up to 256G)

Microphone Support

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC,HLC, ROI, H.265+
COMP-3D DNR, BLC, ROI, H.265+
COMP-3D DNR, BLC, ROI, H.265+
COMP- DarkFighter

3D DNR, BLC, H.265+ COMP

61

62

63

64

Click for More
information

DS-2CD2743G2-IZS

DS-2CD2783G2-IZS

DS-2CD2785G1-IZS

DS-2CD2443G0-IW(W)



Price (Rials)

۱۴۹,۰۰۰,۰۰۰

۱۳۹,۷۲۰,۰۰۰

۱۵۰,۳۲۰,۰۰۰

۶۲,۴۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Cube

Imaging Sensor

1/3" Prog. CMOS

1/2" Prog. CMOS

1/2" Prog. CMOS

1/3" Prog. CMOS

Resolution

4MP (2560x1440/20FPS)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2688x1520/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.008Lux @ F1.2

0.008Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8/4 mm Fixed

Viewing Angle

104°~29°

112°~46°

112°~46°

98°/78

IR Range

Up to 40m

Up to 30m

Up to 30m

Up to 10m

Body Type & Standard

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Plastic

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, H.265+ COMP,
Deep Learning3D DNR, BLC, ROI, H.265+
COMP- DarkFighter3D DNR, BLC, ROI, H.265+
COMP- DarkFighter3D DNR, BLC, HLC, H.265+
COMP, PIR

65

66

67

68

69

70

Click for More
information

DS-2SE4C225MWG-E

DS-2DE4225IW-DE T5

DS-2SE4C425MWG-E(14f0)

DS-2DE4425IW-DE T5

DS-2DE7A432IW-AEB(T5)

DS-2CD2955FWD-IS



Price (Rials)

۲۸۸,۳۴۰,۰۰۰

۲۱۹,۶۲۰,۰۰۰

۳۲۹,۰۰۰,۰۰۰

۲۵۲,۱۵۰,۰۰۰

۴۲۰,۹۸۰,۰۰۰

۱۰۲,۹۶۰,۰۰۰

Camera Type

PTZ

PTZ

PTZ

PTZ

PTZ

Fisheye

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS(Bullet)
1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

2MP(1920x1080/60FPS)

2MP(1920x1080/60FPS)

4MP(2560x1440/60FPS)

4MP(2560 × 1440/30FPS)

4MP(2560 × 1440/30FPS)

5MP(2560 × 1920/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005Lux/F1.0
0.005Lux/F1.6

0.005Lux/F1.6

0.0005Lux/F1.0
0.005Lux/F1.6

0.005Lux/F1.6

0.005Lux/F1.5

0.01Lux/F1.2

Lens

2.8mm (Bullet)
4.8-120mm Motorized

4.8-120mm Motorized

2.8mm (Bullet)
4.8-120mm Motorized

4.8-120mm Motorized

5.9-188.8mm Motorized

1.05mm

Viewing Angle

106°(Bullet)
25x (PTZ)

25x

96.1°(Bullet)
25x (PTZ)

25x

32x

180°

IR Range

Up to 30m(Bullet)
Up to 100m

Up to 100m

Up to 30m(Bullet)
Up to 100m

Up to 100m

Up to 200m

Up to 8 m

Body Type & Standard

Metal/IP66

Metal/IP66

Metal/IP66

Metal/IP66

Metal/IP66, IK10

Metal

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 128G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12 VDC & POE(802.3at)

12 VDC & POE(802.3at)

12 VDC & POE(802.3at)

12 VDC & POE(802.3at)

24 VAC & Hi-POE

12VDC & POE(802.3at)

Other Features

16x Digital Zoom, H.265+, HLC,
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,
BLC, 3D DNR, DarkFighter

3D DNR, H.265+, Anti-flicker

	71	72	73	74	75	76
Click for More information	DS-7104NI-Q1/M	DS-7108NI-Q1/M	DS-7604NI-K1	DS-7604NI-K1/4P	DS-7608NI-Q1	DS-7608NI-K1



Price (Rials)	۴۲,۳۸۰,۰۰۰	۴۹,۳۸۰,۰۰۰	۵۳,۵۲۰,۰۰۰	۸۲,۷۴۰,۰۰۰	۵۸,۳۰۰,۰۰۰	۶۸,۳۴۰,۰۰۰
NVR Type	4 Ch	8 Ch	4 Ch	4 Ch / 4 POE	8 Ch	8 Ch
Input BandWidth	40Mbps	60Mbps	40Mbps	40Mbps	80Mbps	80Mbps
Output Bandwidth	60Mbps	60Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 4Mp	Upto 4Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	-	-	4 POE Ports	-	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 8TB	1 HDD up to 8TB	1 HDD up to 8TB	1 HDD up to 8TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP Alarm I/O 4/1

77

78

79

80

81

82

Click for More
information

DS-7608NI-K2

DS-7608NI-K1/8P

DS-7616NI-Q2

DS-7716NI-Q4/16P

DS-7616NI-K1

DS-7616NI-K2



Price (Rials)

۷۱,۲۰۰,۰۰۰

۱۲۶,۱۹۰,۰۰۰

۸۹,۸۱۰,۰۰۰

۲۵۵,۱۴۰,۰۰۰

۸۵,۸۰۰,۰۰۰

۸۲,۹۷۰,۰۰۰

NVR Type

8 Ch

8 Ch / 8 POE

16 Ch

16 Ch / 16 POE

16 Ch

16 Ch

Input BandWidth

80Mbps

80Mbps

160Mbps

160Mbps

160Mbps

160Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

-

8 POE Ports

-

16 POE Ports

-

-

SATA Interface

1 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 8TB

4 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

1U

1.5U

Standalone 1U

1U

Other Features

H.265+ COMP
Alarm I/O 4/1H.265+ COMP
Alarm I/O 4/1

H.265+ COMP

H.265+ COMP
Alarm I/O 16/4

H.265+ COMP

H.265+ COMP

	83	84	85	86	87	88
Click for More information	DS-7616NXI-K2	DS-7616NI-K2/16P	DS-7616NXI-K2/16P	DS-7716NI-K4	DS-7716NXI-K4	DS-7732NI-K4



Price (Rials)	۹۴,۲۸۰,۰۰۰	۱۸۷,۸۶۰,۰۰۰	۱۸۹,۹۷۰,۰۰۰	۱۸۹,۹۷۰,۰۰۰	۱۹۲,۶۶۰,۰۰۰	۲۱۰,۴۵۰,۰۰۰
NVR Type	16 Ch	16 Ch / 16 POE	16 Ch / 16 POE	16 Ch	16 Ch	32 Ch
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps	256Mbps
Output Bandwidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 12Mp	Upto 8Mp	Upto 12Mp	Upto 8Mp	Upto 12Mp	Upto 8Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	16 POE Ports	16 POE Ports	-	-	-
SATA Interface	2 HDD up to 10TB	2 HDD up to 10TB	2 HDD up to 10TB	4 HDD up to 10TB	4 HDD up to 10TB	4 HDD up to 8TB
Network Interface	2 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Chassis	1U	1U	1U	1.5 U	1.5 U	19" 1.5 Case
Other Features	H.265+ COMPR Alarm I/O 4/1 - Facial Recognition	H.265+ COMPR	H.265+ COMPR Alarm I/O 4/1 - Facial Recognition	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4- Facial Recognition	H.265+ COMPR Alarm I/O 16/4


	89	90	91	92	93	94
Click for More information	DS-7732NI-K4/16P	DS-7732NXI-K4	IDS-7732NXI-I4/8S	DS-9632NI-I8	IDS-9632NXI-I8/4F	DS-9632NXI-I8/S



Price (Rials)	۳۳۴,۳۱۰,۰۰۰	۲۳۱,۱۰۰,۰۰۰	۷۱۹,۱۶۰,۰۰۰	۷۱۰,۰۰۰,۰۰۰	۳,۲۱۳,۸۹۰,۰۰۰	۷۳۹,۰۲۰,۰۰۰
NVR Type	32 Ch / 16 POE	32 Ch	32 Ch	32 Ch	32 Ch	32 Ch
Input BandWidth	256Mbps	256Mbps	320Mbps	320Mbps	320Mbps	320Mbps
Output Bandwidth	160Mbps	160Mbps	256Mbps	256Mbps	256Mbps	256Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out
Decoding Capacity	Upto 8Mp	Upto 12Mp	Upto 12Mp	Upto 12Mp	Upto 12Mp	Upto 12Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P
POE Ports	16 POE Ports	-	-	-	-	-
SATA Interface	4 HDD up to 8TB	4 HDD up to 10TB	4 HDD up to 10TB	8 HDD up to 10TB	8 HDD up to 10TB	8 HDD up to 10TB
Network Interface	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Chassis	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	2U	2U
Other Features	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/8 - Esata 1- DeepinMind	H.265+ COMPR Alarm I/O 16/4, RAID	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1

Click for More
information

IDS-9664NXI-I8/S



Price (Rials)

۹۶۸,۶۳۰,۰۰۰

NVR Type

64 Ch

Input BandWidth

320Mbps

Output Bandwidth

256Mbps

Audio Input/Output

1Ch. In/ 2Ch. Out

Decoding Capacity

Upto 12Mp

Video Output

2 Port HDMI : 4K/1080P
2 Port VGA : 1080P

POE Ports

-

SATA Interface

8 HDD up to 10TB

Network Interface

2 RJ45 1000M

Chassis

2U

Other Features

H.265+ COMPR
Alarm I/O 16/8, RAID,
DeepinMind